



<u>AAMA 1503-09 THERMAL PERFORMANCE TEST</u>		
1. Condensation resistance factor - Frame (CRF)		32
2. Condensation resistance factor - Glass (CRF)		67
3. Thermal transmittance due to conduction (U-Value)		.43

**SELF-FLASHING, THERMALLY BROKEN ACRYLIC SKYLIGHT, WITH INSULATED CURB - SPECIFICATION:**

Self-Flashing Acrylic (dome or pyramid as an option) skylights, ORCA Manufacturing, Inc., Model SFA-TB - 9ISC (6" and 12" curbs available as an option) shall be factory assembled units, each consisting of acrylic domes or pyramids, with .072 extruded glazing sash with weep holes to divert condensation to the outside and with extruded aluminum glazing retaining angle. Each unit will have a built-in evaporative condensation gutter. Insulated curbs shall be of double wall construction of corrosion resistant aluminum connected at top and bottom with thermal barriers. Units shall have a 3" mounting flange for installation to roof deck. Above is of all welded construction.

NOTE: Glazing materials are NOT designed to support the weight of a person. Fall protection may be required and is available as an option.

<b>SFA-TB-9ISC-PYR</b>					
Model	Dimensions (R.O.)	Glazing	Finish	Quantity	Project



**TITLE: SELF-FLASHING ACRYLIC, THERMALLY BROKEN INSULATED CURB - PYRAMID**

Rev. Date	April 18, 2012	
Drawn By	AP	Sheet: 1 OF 1
Rev. By	CRH	Dwg No. SFA-TB-ISC-PYR 041612
Engineer:	AP	

ORCA Manufacturing, inc.  
P.O. Box 992  
Hurlock, MD 21643  
PHONE (800) 776-1539  
FAX (410)-943-8245  
www.starlightskylights.com