



SELF-FLASHING, THERMALLY BROKEN ACRYLIC SKYLIGHT, WITH INSULATED CURB - SPECIFICATION:

Self-Flashing Acrylic (dome or pyramid as an option) skylights, ORCA Manufacturing, Inc., Model SFA-TB - 9ISC (6" and 12" curbs available as an option) shall be factory assembled units, each consisting of acrylic domes or pyramids, with .072 extruded glazing sash with weep holes to divert condensation to the outside and with extruded aluminum glazing retaining angle. Each unit will have a built-in evaporative condensation gutter. Insulated curbs shall be of double wall construction of corrosion resistant aluminum connected at top and bottom with thermal barriers. Units shall have a 3" mounting flange for installation to roof deck. Above is of all welded construction.

NOTE: Glazing materials are NOT designed to support the weight of a person. Fall protection may be required and is available as an option.

SFA-TB-9ISC					
Model	Dimensions (R.O.)	Glazing	Finish	Quantity	Project
		TITLE: SELF-FLASHING ACRYLIC THERMALLY BROKEN INSULATED CURB			
		Rev. Date	April 16, 2012		Sheet: 1 OF 1
		Drawn By	AP	Dwg No.	
		Rev. By	CRH	SFA-TB-ISC 041612	ORCA Manufacturing, inc. P.O. Box 992 Hurlock, MD 21643 PHONE (800) 776-1539 FAX (410)-943-8245 www.starlightskylights.com
Engineer:	AP				